



Product Specifications

FS1285



Fuel/Water Separator, Spin-On

Fleetguard® FS1285 premium fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Largest OD	5.05 inch / 128.26 mm	Length	10.97 inch / 278.76 mm
EMULSIFIED WATER SEPARATION	98	Hydrostatic Burst Minimum	51.62 psi / 355.98 kpa
Rated Flow	39.89 gpm / 151.00 L/min		

Product Comments

Suitable for fuel island applications only for either Gas or Diesel

Related Parts

Filter Used With	HH6951 HH6962	HH6957	HH6967	HH6973
Uses Service				

Part 3929251S
Replaces ST1330

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved