



Product Specifications

LF16015



Lube Filter, Spin-On

Fleetguard® LF16015 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	M27X2-6H	Gasket Inside Diameter	2.46 inch / 62.60 mm
Largest OD	3.69 inch / 93.60 mm	Length	6.96 inch / 176.78 mm
Standpipe	No	Test Specification	ISO 4548-12
Media Type	Stratapore		

Related Parts

Replaces	LF3886
For European Version, Use	LF16519

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of

intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved