



Product Specifications

LF17356



Lube Filter, Spin-On

Fleetguard® LF17356 depth element lube filter incorporate superior filtration techniques to target the root of wear-causing particulate, namely soot.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	M67 X 4 SPECIAL BUTT	Length	6.21 inch / 157.73 mm
Gasket Inside Diameter	1.97 inch / 50.06 mm	Gasket OD	2.30 inch / 58.50 mm
Seam OD	4.00 in / 101.50 mm	Efficiency	97%
Standpipe	NO		

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the

exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved