



Product Specifications

LF17503



Lube Filter, Spin-On

Fleetguard® LF17503 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Gasket OD	4.02 inch / 102.00 mm	Length	10.24 inch / 260.10 mm
Largest OD	4.33 inch / 110.00 mm	Efficiency Test Std	ISO 4548-12
Rated Flow	24.57 gpm / 93.00 L/min	Gasket Inside Diameter	3.70 inch / 94.00 mm
Pressure Valve	No	Primary Particle Efficiency	24.60 micron (c) @ 95%
Media Type	Cellulose	Test Specification	ISO 4548-12
Thread Size	1.125-16 UNF 2B		

Product Comments

Compatible with Euro 6 oils

Related Parts

Is European Version Of	LF3675
Upgrade Of	LF3675

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved