



Product Specifications

LF17505



Lube Filter, Spin-On

Fleetguard® LF17505 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Gasket OD	4.02 inch / 102.00 mm	Largest OD	4.33 inch / 110.00 mm
Length	10.24 inch / 260.10 mm	Efficiency Test Std	ISO 4548-12
Rated Flow	9.25 gpm / 35.00 L/min	Gasket Inside Diameter	3.70 inch / 94.00 mm
Pressure Valve	No	Media Type	Cellulose
Test Specification	ISO 4548-12	Thread Size	1.125-16 UNF 2B

Product Comments

Compatible with Euro 6 oils

Related Parts

Upgrade Of LF3321
Is European Version Of LF3321

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved