



Product Specifications

LF3829



Lube Filter, Cartridge

Fleetguard® LF3829 premium cartridge oil filter is environmentally friendly and features technology advances to achieve the high flow rates required by today's modern engine designs.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

| | | | |
|---------------------|-----------------------|-----------------------------|--------------------------|
| Largest OD | 4.69 inch / 119.00 mm | Length | 12.40 inch / 315.00 mm |
| Efficiency Test Std | ISO 4548-12 | Gasket Inside Diameter | 2.20 inch / 55.80 mm |
| Pressure Valve | No | Primary Particle Efficiency | 39.00 micron (c) @ 98.7% |
| Test Specification | ISO 4548-12 | | |

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved

