



Product Specifications

LF3854



Lube Filter, Spin-On

Fleetguard® LF3854 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Gasket OD	4.49 inch / 114.00 mm	Largest OD	4.80 inch / 122.00 mm
Length	4.75 inch / 120.65 mm	Efficiency Test Std	ISO 4548
Rated Flow	3.96 gpm / 15.00 L/min	Gasket Inside Diameter	3.86 inch / 98.00 mm
Pressure Valve Opening Pressure	98.00 kPa	Hydrostatic Burst Minimum	213.30 psi / 1471.00 kPa
Primary Particle Efficiency	38.00 micron (c) @ 98.7%	Media Type	Cellulose
Test Specification	ISO 4548	Thread Size	1.00 1/2-12 UNF 2B

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the

Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved