



Product Specifications

LF4054



Lube Filter, Spin-On

Fleetguard® LF4054 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	1-12 UNF 2B	Gasket Inside Diameter	2.44 inch / 62.00 mm
Length	8.27 inch / 210.10 mm	Largest OD	3.68 inch / 93.50 mm
Efficiency Test Std	ISO 4548-12	Pressure Valve	Yes
Primary Particle Efficiency	48.00 micron (c) @ 98.7%	Test Specification	ISO 4548-12
Media Type	Cellulose		

Product Comments

For removal nut, see LF3625.

Related Parts

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved