



Product Specifications

LF691A



Lube Filter, Spin-On

Fleetguard® LF691A spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	1.00 1/2-16 UNF 2B	Gasket OD	4.29 inch / 108.97 mm
Gasket Inside Diameter	3.72 inch / 94.49 mm	Length	12.19 inch / 309.65 mm
Largest OD	5.38 inch / 136.61 mm	Hydrostatic Burst Minimum	199.95 psi / 1379.00 kPa
Rated Flow	28.01 gpm / 106.00 L/min	Primary Particle Efficiency	25.00 micron (c) @ 99.75%

Related Parts

For Upgrade, Use	LF9691A	LF3566
Uses Service Part	3838290S	
Replaces	LF3954	

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a

convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved