



# Product Specifications

## LF9009



### Lube Filter, Spin-On

Fleetguard® LF9009 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](http://Fleetguard.com)

## Specifications

Thread Size	2.25-12 UNF 2B	Media Type	StrataPore
Largest OD	4.68 inch / 118.87 mm	Length	11.88 inch / 301.76 mm
Gasket Inside Diameter	4.01 inch / 101.85 mm	Gasket OD	4.68 inch / 118.87 mm
Efficiency Test Std	CECO 10765	Rated Flow	27.74 gpm / 105.00 L/min
Pressure Valve	No	Test Specification	CECO 10765
Length / Overall Height	11.82 inch / 300.28 mm		

## Related Parts

**For Upgrade, Use  
Upgrade Of**

LF14002NN  
LF3000

LF14009NN

<b>Primary Applications</b>	TECXLF7000
<b>Is An Exact Match W/Diff Gasket</b>	LF9039
<b>Filter Used With</b>	3934644S

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved