



Product Specifications

LF9050



Lube Filter, Spin-On

Fleetguard® LF9050 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	M90X2-7H	Media Type	StrataPore
Length	11.71 inch / 297.38 mm	Largest OD	4.72 inch / 119.88 mm
Gasket Inside Diameter	4.00 inch / 101.60 mm	Gasket OD	4.74 inch / 120.30 mm
Efficiency Test Std	CECO 10765	Pressure Valve	No
Primary Particle Efficiency	24.60 micron (c) @ 98.7%	Test Specification	CECO 10765

Product Comments

Venturi Combo Filter with Stratapore media

Related Parts

For Upgrade, Use	LF14005NN	
Replaces	3919823	LF9024

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved