



APPLICATIONS

Eni Rotra ATF III is a lubricant for automatic transmissions and power steering gears, specifically formulated to comply with the most demanding specifications of the main American and European OEMs.

CUSTOMER ADVANTAGES

- **Eni Rotra ATF III** has an excellent oxidation stability, preventing deterioration of lubricant from high temperature operations, and the formation of sludge.
- A balanced set of friction modifiers provides a outstanding transmission efficiency and smooth, silent gear shifting.
- **Eni Rotra ATF III** ensures a complete compatibility with a wide range of elastomers and metal alloys, very good cold properties and high antiwear properties for all contact surfaces.
- Although the product **Eni Rotra ATF III** is not officially approved by Allison, it can be utilized in all those cases where the vehicle manufacturer requires for the transmission a product with Allison C-4 or TES 389 performance level.

SPECIFICATIONS

- Ford MERCON
- GM DEXRON III H





CHARACTERISTICS

Properties	Method	Unit	Typical
Colour	-	-	red
Density at 15°C	ASTM D 4052	kg/m ³	845
Viscosity at 100°C	ASTM D 445	mm ² /s	7.1
Viscosity at -40°C	ASTM D 2983	mPa·s	16000
Viscosity Index	ASTM D 2270	-	180
Flash point COC	ASTM D 92	°C	205
Pour point	ASTM D 97	°C	-48
Sulphur	ASTM D 4951	% m/m	0.126

