



BARDAHL TECHNOS C60 5W30 mSAPS

TECHNOS C60 mSAPS is a PREMIUM PERFORMANCE lubricant for the latest generation of gasoline and diesel engines equipped with exhaust gas post-treatment systems requiring lubricants with low contents of SAPS.

Thanks to its specific additives, **mSAPS**, with low contents of sulphur, phosphorus and sulphated ashes, extends the life of the anti-particulate filters (FAP and DPF) and catalytic exhausts.

The precious synthetic bases and the special blending high stability polymers used in its formula, give **TECHNOS C60 mSAPS** extraordinary properties of resistance to the thermal deterioration due to oxidation, tenacity of the lubricating oil film and fluidity at low temperatures.

TECHNOS C60 mSAPS also guarantees a superior control of deposits, sludge and wear, thus allowing the engine to offer and preserve its original maximum mechanical performance.

TECHNOS C60 mSAPS helps to efficaciously fight against wear due to oil dilution with fuel and dirt in the engine caused by the use of bio-diesel in the gas oil.

Properties

- Superior control of wear, even in case of contamination of the oil with the fuel
- Longer life and higher cleanliness of all parts of the engine
- It protects the operation of anti-particulate filters and catalytic exhausts
- Easy start and immediate lubrication at low temperatures. Helps fuel economy
- Its low evaporation properties help to reduce the oil consumption
- Longer intervals between oil changes
- It efficaciously fights against the premature deterioration of the oil caused by bio-diesel
- Formulated with fully synthetic bases

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



BARD AHL TECHNOS C60 5W30 mSAPS

PERFORMANCE LEVEL

API SN-CF / ACEA C3 / MB 229.51 / BMW Longlife 04 / GM dexos 2

CHEMICAL-PHYSICAL CHARACTERISTICS

Viscosity at 40°C	74,7 cSt
Viscosity at 100°C	12,4 cSt
Density at 15°C	0,852 kg/l
Viscosity index	168
Flash point	206°C
Pour point	-42°C
T.B.N.	7,7 (mg KOH/g)

The values shown in this table are just as an indication, variable within certain tolerances.

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045