



XTS 0W20

DESCRIPTION

New generation fully synthetic engine oil, developed to ensure a clean engine.

APPLICATION

BARD AHL XTS 0w20 improves fuel economy, increases piston cleanliness, reduces emissions, and protects against wear and the formation of muds. It can be used in turbocharged hybrid-petrol engines. It is compatible with E85 fuel. Bardahl XTS 0w20 is suitable for modern hybrid vehicles.

SPECIFICATIONS

This product offers the following performance level:

ILSAC	GF-7B
API	SQ-RC (Resource Conserving)
GM	Dexos 1™ Gen 3
GM	6094M
CHRYSLER	MS 6395
FORD	WSS-M2C947-A/B1 WSS-M2C962-A1
FIAT	9.55535-CR1

PROPERTIES

- ✓ Offers stable viscosity and a high viscosity index
- ✓ Provides a good resistance against « shearing »
- ✓ Makes cold start easier
- ✓ Limits fuel overconsumption
- ✓ Offers excellent resistance against oxidation
- ✓ Leaves a lubricating film preserved at high temperature
- ✓ Has excellent dispersion and cleaning properties



TECHNICAL DATA SHEET 082025

TECHNICAL DATA

Density at 20°C	Kg/l	0,844
Viscosity dynamic CCS	cP	5740
Viscosity at 40°C	mm ² /s	44,5
Viscosity at 100°C	mm ² /s	8,4
Viscosity Index		168
Flash point COC, °C	°C	226
Pour point, °C	°C	-42
TBN alcalinity	mgKOH/g	7,4
Sulfated ash contents	%	0,78

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by incompleteness or incorrectness will be accepted.

RECOMMANDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

Storage: it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36331	12 x 1L
36332	4 x 4L
36333	3 x 5L
36334	60L
36337	205L