



# XTEC 5W30 C2

## DESCRIPTION

Synthetic engine oil with low ash content, "Fuel economy" formulated from last generation additives and specially developed for vehicles equipped with a particle filter (DPF), conforming to the EURO IV et EURO V norms.

## APPLICATION

**BARD AHL XTEC 5w30 C2** has been developed according to the Mid S.A.P.S/High HTHS technology. It is a very high performance and low viscosity lubricant, formulated to limit fuel overconsumption and exhaust emissions. Particularly suitable for the last generation vehicles equipped with 3 way-catalytic converters and particulate filter.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	C2
API	SN/CF
RENAULT	RN 0700
FIAT	9.55535-S1
PSA	B71 2290

## PROPERTIES

- ✓ Avoids fuel overconsumption,
- ✓ Compatible with modern catalytic converters,
- ✓ Forms a lubricating film protecting the engine at high temperature,
- ✓ Extends the drain intervals,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier,
- ✓ Provides a high protection against corrosion, wear and the formation of foam.



## TECHNICAL DATA

<b>Density at 15°C</b>	Kg/l	0,853
<b>Viscosity at -35°C</b>	mPa.s	5390
<b>Viscosity at 40°C</b>	mm <sup>2</sup> /s	63
<b>Viscosity at 100°C</b>	mm <sup>2</sup> /s	10,90
<b>Viscosity Index</b>		166
<b>Flash point COC, °C</b>	°C	230
<b>Pour point, °C</b>	°C	-42
<b>TBN alcalinity</b>	mgKOH/g	7,7
<b>Sulphated ash contents</b>	%	0,8

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36531	12 x 1 L
36532	4 x 4 L
36533	3 x 5 L
36538	20 L
36534	60 L
36537	205 L