



Product Specifications

FF5021



Fuel Filter, Spin-On

Fleetguard® FF5021 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	13/16-12 UNS-2B	Gasket OD	3.49 inch / 88.57 mm
Gasket Inside Diameter	3.11 inch / 79.12 mm	Length	4.31 inch / 109.46 mm
Largest OD	3.69 inch / 93.72 mm	Standpipe	No
Efficiency Test Std	SAE J905	Primary Particle Efficiency	17.30 micron (c) @ 96%
Rated Flow	1.50 gpm / 5.67 L/min	Media Type	Cellulose
Applicable Region	North America, China, Europe, South America, South East Asia, South Pacific, Mexico and Central America		

Related Parts

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved