

# ALPINE® PSA 0W-30

## High-performance low viscosity engine oil for passenger car engines

### Properties

**ALPINE PSA 0W-30** is a modern high-performance low viscosity engine oil for petrol and diesel engines in passenger cars. Thanks to its special formulation, **ALPINE PSA 0W-30** guarantees maximum thermal and mechanical stability, excellent viscosity-temperature behavior and a low vaporisation inclination. Maximum protection against wear and excellent low-temperature properties ensure optimal lubricating reliability in the cold running phase and minimum cold start wear.

### Application notes

**ALPINE PSA 0W-30** is suitable for modern car engines of the latest technology, especially those with automatic start and stop.

**Observe manufacturer's instructions!**

### Service description

#### Specifications:

- ACEA C1/C2
- JASO DL-1

#### Recommendations\*:

- PSA B71 2312, PSA B71 2302
- Jaguar Land Rover STJLR.03.5007
- Fiat 9.55535-DS1
- Fiat 9.55535-GS1
- IVECO 18-1811 Classe SC1 LV

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE PSA 0W-30
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	843
Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	53.9
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	10.0
Viscosity index (VI)	DIN ISO 2909	-	175
Viscosity at -35°C	DIN 51562	mPa.s	5800
Pour point	DIN ISO 3016	°C	-51
TBN	DIN ISO 3771	mg KOH/g	6.3

\* meets the requirements of the OEM manufacturer.  
The stated values may vary within the usual commercial range.