

# ALPINE® Special V 0W-30

**Synthetic high-performance low viscosity engine oil for Volvo passenger cars**

## Properties

**ALPINE Special V 0W-30** is a synthetic high-performance low viscosity engine oil. The lowered HTHS viscosity enables fuel savings in the cold start phase and in short-distance traffic. Guarantees highest engine cleanliness and best wear protection. The product is suitable for use in Volvo passenger cars with the latest efficiency-enhanced Euro 4, 5, 6 engine concepts with or without turbocharger, direct injection, multi-valve or hybrid technology. **ALPINE Special V 0W-30** guarantees a fuel-saving potential and contributes to the protection of the environment by reducing CO2emissions.

## Application notes

**ALPINE Special V 0W-30** is recommended for modern gasoline and diesel engines with the specification VOLVO VCC 95200377.

## Service description

### Specifications:

- ACEA A5/B5
- API SL

### Recommendations\*:

- Volvo VCC 95200377

| TYPICAL PARAMETERS   | METHODS      | UNITS              | ALPINE Special V 0W-30 |
|----------------------|--------------|--------------------|------------------------|
| Density at 15°C      | DIN 51 757   | kg/m <sup>3</sup>  | 844                    |
| Viscosity at 40°C    | DIN 51 562   | mm <sup>2</sup> /s | 53.2                   |
| Viscosity at 100°C   | DIN 51 562   | mm <sup>2</sup> /s | 10.0                   |
| Viscosity Index (VI) | DIN ISO 2909 | -                  | 180                    |
| Viscosity at -35°C   | DIN 51 377   | mPa.s              | 6000                   |
| Pour point           | DIN ISO 3016 | °C                 | -39                    |
| Flash point COC      | DIN ISO 2592 | °C                 | 220                    |

\* meets the requirements of the OEM manufacturer.  
The stated values may vary within the usual commercial range.