



Product Specifications

AF26199



Air Filter, Primary

Fleetguard® AF26199 axial seal primary air filter ensures a proper seal and prevent leaks to prevent airborne contaminants from reaching the combustion chamber.

[View product on Fleetguard.com](#)

Specifications

Largest ID	5.91 inch / 150.00 mm	Height	16.36 inch / 415.50 mm
Largest OD	9.09 inch / 231.00 mm	Length	16.30 in / 414.50 mm
Efficiency Test Std	ISO 5011	Full Life Efficiency	99.95
Media Type	Cellulose		

Product Comments

Flame Retardant Media

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of

intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved