



Product Specifications

AF409K



Air Filter, Primary

Fleetguard® AF409K axial seal primary air filter ensures a proper seal and prevent leaks to prevent airborne contaminants from reaching the combustion chamber.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Largest ID	3.48 inch / 88.40 mm	Height	12.42 inch / 315.50 mm
Fin Diameter	7.85 inch / 199.50 mm	Largest OD	6.08 inch / 154.40 mm
Flame Resistant Media	No	Flow Direction	Outside In
Type Seal	Axial	Rated Flow	8.00 CU. m/m
Full Life Efficiency	100		

Product Comments

Some European applications use AF1980. For Magnum Version, use AF409KM. 3311624 Bolt Seal Included

Related Parts

Primary Air Filter Used With	AF1980	AF4813
Filter Used With	AH19110	
For Flame Retardant Version, Use	AF4941K	

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved