



Product Specifications

FF105



Fuel Filter, Spin-On

Fleetguard® FF105 fuel filter cartridge reduces contamination, trapping dirt particles and preventing them from reaching the moving parts in your engine supporting longer service intervals.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Largest OD	3.69 inch / 93.78 mm	Length	5.41 inch / 137.41 mm
Gasket Inside Diameter	2.46 inch / 62.53 mm	Gasket OD	2.83 inch / 71.99 mm
Efficiency Test Std	SAE J905	Standpipe	No
Primary Particle Efficiency	17.30 micron (c) @ 96%	Rated Flow	348.00 L/min
Test Specification	SAE J905	Media Type	Cellulose

Product Comments

Extended Life Version of FF104 w/o drain For Synthetic Media Version, use FF5332.

Related Parts

Upgrade Of	FF104	
Uses Service Part	154711S	255622S
Is A Shorter Version Of	FF213	
For Upgrade, Use	FF5332	FS1212
Filter Used With	142784S	212013S
Uses Service Gasket	3301519	3930618S

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved