



Product Specifications

FS1240



[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	1-14 UNS-2B	Largest OD	3.66 inch / 93.04 mm
Length	3.86 inch / 98.04 mm	Gasket OD	2.83 inch / 71.98 mm
Gasket Inside Diameter	2.46 inch / 62.53 mm	Standpipe	NO
Test Specification	SAE J905	Hydrostatic Burst Minimum	89.98 psi / 620.55 kPa
Primary Particle Efficiency	17.30 micron (c) @ 96%		

Product Comments

Outside/In Flow Version of FS1233 Must be used with Fleetguard head. Bowl not included

Related Parts

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved