



Product Specifications

FS1287



Fuel/Water Separator, Spin-On

Fleetguard® FS1287 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

| | | | |
|-----------------------------|--------------------------|--------------------|-----------------------|
| Thread Size | 1-14 UNS-2B | Length | 5.04 inch / 128.14 mm |
| Largest OD | 4.35 inch / 110.50 mm | Gasket OD | 3.58 inch / 91.00 mm |
| Standpipe | NO | Test Specification | ISO 19438 |
| Primary Particle Efficiency | 24.60 micron (c) @ 98.7% | | |

Product Comments

For drain only version with no sensor port, use FS19930.

Related Parts

Uses Service Part 3948395S

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved