



Product Specifications

HF7071

Hydraulic Filter, Cartridge



Fleetguard® HF7071 hydraulic cartridge filter with synthetic media is designed to help keep your precision hydraulic systems running as intended, providing a solution for various applications. This filter meets or exceeds the equipment OEM quality and performance and is the first aftermarket replacement available on the market today, bringing your operation top-quality performance and an overall unbeatable total cost of ownership.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Largest OD	3.12 inch / 79.30 mm	Length	8.19 inch / 208.03 mm
Efficiency Test Std	ISO 4572	Particle Size at Beta 200	24.60 Micron
Particle Size at Beta 75	20.90 Micron	Rated Flow	21.40 gpm / 81.00 L/min
Element Collapse/Burst, Min	1034.00 kPa	Test Specification	ISO 4572
Largest End ID	1.67 inch / 42.42 mm	Length / Overall Height	8.19 inch / 208.03 mm

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Atmus Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2026 Atmus Filtration Technologies Inc. All Rights Reserved